

SPECTRUM ARCHITECTURAL SPECIFICATION

Model 11236-UI

August 1, 2005

PART 1 GENERAL

1.1 GENERAL

- 1.1.1 Scoreboard(s) shall be UL Listed and be remotely operated via three-wire shielded grounded cable from control point(s). Scoreboard(s) shall display the following information: Minutes, Seconds and Score to 99 for two teams as well as Quarter, Ball Possession and TOL (time outs left) for each team, Down, (yards) To Go and Ball On. Equipment to be solid-state electronic technology.

PART 2 PRODUCT

2.1 SCOREBOARD

- 2.1.1 Shall be Spectrum Model 11236-UI or approved equal to this specification by the architect. Provide ____ units of this model.
- 2.1.2 Overall cabinet shall be 10 feet in height by 36 feet in length by 5 inches in depth including mounting brackets, cabinet face constructed of 18 gauge steel and cabinet shell constructed of .050 aluminum. Cabinet color shall be as selected from the manufacturers standard colors with appropriate trim colors. Nine horizontal cabinets to be shipped and constructed for four-column mounting with one bottom and one top steel mounting bracket supplied by manufacturer. Approximate weight is ____ pounds.
- 2.1.3 Display digits shall be constructed of 22 gauge galvanized steel. Lamp sockets shall be the porcelain, non-slip, brass shell, self-locking type. Display digits shall be made up of 15-watt inside frost standard lamps. All lamps shall be housed in round, black, self-locking, copolymer polypropylene tube to maximize the lamp brilliance and enhance angle readability. Digit height shall be 30 inches for Clock and Team Scores; 24 inches for Down, To Go, Quarter, Ball On and TOL (Time Out Left). Game Clock shall have a display capacity up to "99:59", team score to "99", TOL to "9", Down to "9", To Go to "99", Quarter to "9" and Ball On to "99".
- 2.1.4 Display configuration shall be 6 x 9 for 30 inches (double-stroked); 4 x 7 for 24 inches.
- 2.1.5 Lampbank sun filter screen shall be constructed of mesh aluminum wire with charcoal epoxy coating permanently attached to a heavy duty anodized aluminum frame.
- 2.1.6 Finish in Two-Component Polyurethane coating.
- 2.1.7 Captions shall be adhesive backed vinyl permanently attached to the cabinet and Home and Visitor shall be 18 inches in height; Down, To Go, Quarter and Ball On shall be 14 inches in height; TOL (time outs left) shall be 12 inches in height.
- 2.1.8 Electronics to be packed in a high voltage plug-in processor accessible from the cabinet back.
- 2.1.9 Power to be 7,800 watts maximum, 120 VAC, 60 Hz.
- 2.1.10 Provide an electronic standard horn rated at 100 dB @ 10'0".

2.2 CONTROL

- 2.2.1 Shall be model MSX housed in a protective, weather resistant carrying case. Construction shall be a plastic case 15 inches long by 3 ¾ inches high by 12 inches deep.
- 2.2.2 Furnished with a 10' low voltage data cable cord to connect to control receptacle junction box and shall unplug and store inside the carrying case. Does NOT require hazardous 120 VAC electrical power.
- 2.2.3 Shall include four lines of 16 large backlit LCD characters showing information as sent to the scoreboard display and allows operator to see LCD in low-light areas.
- 2.2.4 A changeable color coded keypad to allow key identification change to operate multiple scoreboards. Electronic features shall include a program mode allowing change in sport controlled or accommodation of a sport rules change and a memory circuit to retain information if power is interrupted.
- 2.2.5 Red LED indicators to indicate clock-running up or down, auto-horn "on" status for end of period and auto-horn "on" status for substitution of players.
- 2.2.6 Switches have a life of at least 5 million operations. All membrane switches shall be "splash-proof" and environmentally sealed by a combination of layers of a velvet-grain, highly durable, polycarbonate and glossy polyester. All switches are defined by the 0.020 velvet-grain polycarbonate "switch locator" overlay. The numeric keypad, on-off rocker clock and score switches shall give "tactile feedback" to the operator.
- 2.2.7 Operating features include cumulative memory, time-of-day display to allow the scoreboard to display time-of-day for non-sport display, tenth-of-a-second timing to allow more accurate timing during last minute of play and track-timing interface to display track-timing information from automatic timing systems on standard football scoreboard.

2.3 REMOTE CONTROL CABLE

- 2.3.1 Furnish one length of three wire-shielded, grounded cable to connect receptacle junction box to the scoreboard cabinet.

2.4 LIMITED WARRANTY

- 2.4.1 Spectrum Solid State Scoreboards are guaranteed for a period of five (5) years (lamp sockets are guaranteed for a period of ten (10) years) against any defects in materials. Urethane Finish is guaranteed for a period of ten (10) years against any defects in materials. First year service includes cost of labor and parts when returned prepaid to Spectrum Corporation. Remaining four (4) years cover parts only, when returned insured, prepaid to Spectrum Corporation. Lamps are not included in the warranty. Warranty does not cover unauthorized repairs or modifications, abuse, neglect, acts of God, exceptionally high or low voltage, and/or improper grounding, installation, operation, or shipment to the factory.

2.5 OPTIONAL EQUIPMENT

- 2.5.1 Provide one MSX Clock Handswitch for second operator.
- 2.5.2 Provide wireless radio control operation for above equipment.
- 2.5.3 Provide Spirit/Sponsor sign panels for above equipment.
- 2.5.4 Provide electronic team names for above equipment.
- 2.5.5 Provide electronic message display board for above equipment.
- 2.5.6 Provide electronic video display board for above equipment.