

SPECTRUM ARCHITECTURAL SPECIFICATION

Model 10308-UI

August 1, 2005

PART 1 GENERAL

1.1 GENERAL

- 1.1.1 Scoreboard(s) shall be UL Listed and be remotely operated via three-wire shielded grounded cable from control point(s). Scoreboard(s) shall display the following information: Home and Visitor Score, 3-Digit Clock, Inning, Ball, Strike, Out, Hit and Error. Time shall be displayed on the top middle section with two sign panels on the right and left of the clock. 3-Digit Time Clock shall display hours and minutes until the last minute when it changes to seconds. Equipment to be solid-state electronic technology.

PART 2 PRODUCT

2.1 SCOREBOARD

- 2.1.1 Shall be Spectrum Model 10308-UI or approved equal to this specification by the architect. Provide ____ units of this model.
- 2.1.2 Overall cabinet shall be 6 feet in height by 8 feet in length by 5 inches in depth including mounting brackets, and constructed of .063 aluminum. Cabinet color shall be as selected from the manufacturers standard colors with appropriate trim colors. Two horizontal cabinets to be shipped and constructed for two-column mounting with two top steel mounting brackets built into the cabinet by the factory and one bottom steel mounting bracket supplied by manufacturer. Approximate weight is ____ pounds.
- 2.1.3 Display digits shall be constructed of 22 gauge galvanized steel. Lamp sockets shall be the porcelain, non-slip, brass shell, self-locking type. Display digits shall be made up of 15-watt inside frost standard lamps. Ball, Strike and Out indicators shall each consist of 15-watt lamp in a three-inch spot. Ball shall be displayed by three indicator spots; and Strike and Out by two indicators spots each. All lamps shall be housed in round, black, self-locking, copolymer polypropylene tube to maximize the lamp brilliance and enhance angle readability. Home and Visitor digits height shall be 18 inches; and Clock and Inning digit height shall be 15 inches. Game clock shall have a display capacity of up to "1:59"; Home and Visitor score up to "99"; and Inning up to "9".
- 2.1.4 Display configuration shall be 3 x 5 for 15 inches and 18 inches.
- 2.1.5 Lampbank sun filter screen shall be constructed of mesh aluminum wire with charcoal epoxy coating permanently attached to a heavy duty anodized aluminum frame.
- 2.1.6 Finish in Two-Component Polyurethane coating.
- 2.1.7 Captions shall be adhesive backed vinyl permanently attached to the cabinet and Home, Visitor, Inning, Ball, Strike and Out shall be 8 inches in height.
- 2.1.8 Electronics to be packed in a high voltage plug-in processor accessible from the cabinet back.
- 2.1.9 Power to be 1,560 watts maximum, 120 VAC, 60 Hz.

2.2 CONTROL

- 2.2.1 Shall be model MSX housed in a protective, weather resistant carrying case. Construction shall be a plastic case 15 inches long by 3 ¾ inches high by 12 inches deep.
- 2.2.2 Furnished with a 10' low voltage data cable cord to connect to control receptacle junction box and shall unplug and store inside the carrying case. Does NOT require hazardous 120 VAC electrical power.
- 2.2.3 Shall include four lines of 16 large backlit LCD characters showing information as sent to the scoreboard display and allows operator to see LCD in low-light areas.
- 2.2.4 A changeable color coded keypad to allow key identification change to operate multiple scoreboards. Electronic features shall include a program mode allowing change in sport controlled or accommodation of a sport rules change and a memory circuit to retain information if power is interrupted.
- 2.2.5 Red LED indicators to indicate clock-running up or down, auto-horn "on" status for end of period and auto-horn "on" status for substitution of players.
- 2.2.6 Switches have a life of at least 5 million operations. All membrane switches shall be "splash-proof" and environmentally sealed by a combination of layers of a velvet-grain, highly durable, polycarbonate and glossy polyester. All switches are defined by the 0.020 velvet-grain polycarbonate "switch locator" overlay. The numeric keypad, on-off rocker clock and score switches shall give "tactile feedback" to the operator.
- 2.2.7 Operating features include cumulative memory, time-of-day display to allow the scoreboard to display time-of-day for non-sport display, tenth-of-a-second timing to allow more accurate timing during last minute of play and track-timing interface to display track-timing information from automatic timing systems on standard football scoreboard.

2.3 REMOTE CONTROL CABLE

- 2.3.1 Furnish one length of three wire-shielded, grounded cable to connect receptacle junction box to the scoreboard cabinet.

2.4 LIMITED WARRANTY

- 2.4.1 Spectrum Solid State Scoreboards are guaranteed for a period of five (5) years (lamp sockets are guaranteed for a period of ten (10) years) against any defects in materials. Urethane Finish is guaranteed for a period of ten (10) years against any defects in materials. First year service includes cost of labor and parts when returned prepaid to Spectrum Corporation. Remaining four (4) years cover parts only, when returned insured, prepaid to Spectrum Corporation. Lamps are not included in the warranty. Warranty does not cover unauthorized repairs or modifications, abuse, neglect, acts of God, exceptionally high or low voltage, and/or improper grounding, installation, operation, or shipment to the factory.

2.5 OPTIONAL EQUIPMENT

- 2.5.1 Provide wireless radio control operation for above equipment.
- 2.5.2 Provide Spirit/Sponsor sign panels for above equipment.